

- ◇ 輸入電壓：DC12V/24V
- ◇ 消耗電流：12V/100mA, 24V/50mA
- ◇ 拉力：約50kg
- ◇ 產品認證：CE合格
- ◇ 使用場所：安全逃生門防煙區
- ◇ 需搭配SAP-702F固定圓鐵板座  
或搭配SAP-702角度調整圓鐵板座
- ◇ 內置突波吸收元件
- ◇ 具備防殘磁頂針
- ◇ 動作訊號：需選購
- ◇ 電源釋放開關：DH-502、DH-504



### ◀ DH-501 (基本型)

80(L)×80(W)×37(H) mm

### DH-502 (牆上型) ▶

90(L)×70(W)×40(H) mm



### ◀ DH-504 (地上型)

118(L)×93(W)×115(H) mm

### DH-505 (埋入型) ▶

120(L)×76(W)×30(H) mm



## 配件鐵板座選擇


### SAP-702 ▶

- ◇ 60×60×54 mm
- ◇ 搭配DH門扣系列



### SAP-702E ▶

- ◇ 外徑Φ92mm
- ◇ 內徑Φ63.3 mm
- ◇ 高24~28.7mm
- ◇ 搭配DH門扣系列



### SAP-702F ▶

- ◇ 60×60×23 mm
- ◇ 搭配DH門扣系列

